



# Valves

Handling the world's dry bulk solids®

## VORTEX® ABRASIVE DUTY GATE™

The Vortex® Abrasive Duty Gate™ is designed to meet the demanding applications associated with handling material such as sand, gravel, whole grains, and coal. The narrow profile, choice of actuators, and custom rectangular size make this slide gate adaptable to most existing installations. Optional round inlets or outlets flanges and dust return pans are also available. Abrasive Duty Gate™ is designed to eliminate problems, enabling you to meet your objectives by increasing production, while decreasing labour and equipment costs.

### Vortex® Abrasive Duty Gate™ Features

- Hardened Steel Rollers with Grease Fittings
- Designed for Tough Abrasive Handling
- Positive Seal of Material
- Seals Protected from Abrasion
- Accurate Metering of Material with Optional Metering Controls
- Easy Installation and Maintenance



### Valve Specifications

Size/Bore Options	150mm to 600mm Square, Rectangular, or Round
Media	Abrasives, Granulars
Connection Options	ANSI 150LB, DIN/PN10/PN40, JIS/10K, Custom Flanges Square or Rectangular
Media Temperature	Up to 82°C continuous to 121°C intermittent service, Modifications allow up to 288°C continuous to 316°C intermittent service.
Media Pressure	0 barg, Gravity Flow Only
Metal Construction Options	304 Stainless Steel, Carbon Steel, and/or Abrasion Resistant Carbon Steel
Seal/Seat Material Options	Nylon, PET, Glass Filled Teflon, Carbon Steel
Drive/Actuation Options	Double Acting Air Cylinder and Solenoid Operated Air Control Valve, Electric Actuator, Hydraulic, Hand Wheel, or Chainwheel
Position Confirmation	Magnetic Reed Switch, Proximity Switch, Mechanical Switch
Compliance/Approvals	CE, ATEX
Industry Use	Plastics, Petrochemicals, Chemicals, Minerals, Textiles, Agriculture



### Application Specific Modifications

SC	Slide Blade and frame are 304 stainless steel. Rollers are 440 stainless steel and roller stud bolts are 304 or 18-8 stainless steel.
MG	Air cylinder has a magnetic ring which activates a magnetic reed position indicating switch.
HT3	Modifications are made allowing 121°C continuous to 149°C intermittent service.
HT4	Modifications are made allowing 204°C continuous to 232°C intermittent service.
HT6	Modifications are made allowing 288°C continuous to 316°C intermittent service.
AR	Slide Blade is made of AR plate for handling more abrasive materials.
DS	The dust seal will help to eliminate or reduce dusting to atmosphere. The Enhanced Bonnet Seal option would be preferred for handling rocks with dust present.